



US009960521B2

(12) **United States Patent**  
**Armstrong et al.**

(10) **Patent No.:** **US 9,960,521 B2**  
(45) **Date of Patent:** **May 1, 2018**

(54) **CONNECTOR FOR FLUIDLY SEALING AN APERTURE OF A PROTECTIVE CASE**

(71) Applicant: **Otter Products LLC**, Fort Collins, CO (US)

(72) Inventors: **Peter S. Armstrong**, Poway, CA (US); **Francisco Garcia**, San Diego, CA (US); **Jonathan Arpin**, San Diego, CA (US); **Warren M. Terry**, Poway, CA (US)

(73) Assignee: **Otter Products, LLC**, Fort Collins, CO (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. days.

(21) Appl. No.: **15/419,844**

(22) Filed: **Jan. 30, 2017**

(65) **Prior Publication Data**

US 2017/0244194 A1 Aug. 24, 2017

**Related U.S. Application Data**

(60) Provisional application No. 62/299,292, filed on Feb. 24, 2016.

(51) **Int. Cl.**  
**H01R 13/52** (2006.01)  
**A45C 11/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H01R 13/5202** (2013.01); **A45C 11/00** (2013.01); **G06F 1/1626** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,164,221 A 6/1939 Hoover et al.  
2,392,787 A 1/1946 Edmond  
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1018680 A2 7/2000  
EP 1939263 A1 7/2008  
(Continued)

OTHER PUBLICATIONS



PCT Intl. Search Report and Written Opinion for PCT Appn. No. PCT/US2011/056040, dated Jul. 12, 2012.  
Results for Invalidity Search for U.S. Pat. No. 6,995,976.

*Primary Examiner* — Tho D Ta

(57) **ABSTRACT**

A protective case for a portable electronic device is provided. The portable electronic device has a device connector for transmission of data and/or power between the device connector and a data and/or power source via a reciprocal connector assembly. The case includes an aperture disposed proximate the device connector of the installed portable electronic device, the aperture passing between an outer surface and an inner surface of the case and defined by a surface between the outer and inner surfaces, the aperture having a circumference; and a compliant seal surrounding the circumference of the aperture, the compliant seal to interface with at least a portion of the backshell portion of the reciprocal connector assembly to seal the aperture when the reciprocal connector assembly is inserted through the aperture to interface with the device connector of the installed portable electronic device.

**17 Claims, 12 Drawing Sheets**



## Page 2

- |      |                       |   |         |                    |   |         |                    |  |
|------|-----------------------|---|---------|--------------------|---|---------|--------------------|--|
| (51) | Int. Cl.              |   |         | 5,508,479          | A | 4/1996  | Schooley           |  |
|      | <i>G06F 1/16</i>      | (2006.01)   |         | 5,541,813          | A | 7/1996  | Sato et al.        |  |
|      | <i>H01R 13/516</i>    | (2006.01)   |         | RE35,318           | E | 8/1996  | Warman             |  |
| (52) | U.S. Cl.              |   |         | 5,548,306          | A | 8/1996  | Yates et al.       |  |
|      | CPC .....             | <i>H01R 13/516</i> (2013.01); <i>H01R 13/5219</i>         |         | 5,573,164          | A | 11/1996 | Law                |  |
|      |                       | (2013.01); <i>A45C 2011/001</i> (2013.01); <i>A45C</i>    |         | 5,583,742          | A | 12/1996 | Noda et al.        |  |
|      |                       | <i>2011/002</i> (2013.01); <i>A45C 2011/003</i> (2013.01) |         | 5,584,054          | A | 12/1996 | Tyneski et al.     |  |
|      |                       |   |         | 5,586,002          | A | 12/1996 | Notarianni         |  |
|      |                       |   |         | 5,586,176          | A | 12/1996 | Peck               |  |
|      |                       |   |         | 5,590,760          | A | 1/1997  | Astarb             |  |
|      |                       |   |         | 5,610,655          | A | 3/1997  | Wakabayashi et al. |  |
|      |                       |   |         | 5,613,237          | A | 3/1997  | Bent et al.        |  |
|      |                       |   |         | 5,632,373          | A | 5/1997  | Kumar et al.       |  |
| (56) | References Cited      |   |         | 5,636,101          | A | 6/1997  | Bonsall et al.     |  |
|      | U.S. PATENT DOCUMENTS |   |         | 5,648,757          | A | 7/1997  | Vernace et al.     |  |
|      | 2,851,670             | A   | 9/1958  | Senior             |   |         |                    |  |
|      | 3,023,885             | A   | 3/1962  | Kindseth           |   |         |                    |  |
|      | 3,143,384             | A   | 8/1964  | Senior             |   |         |                    |  |
|      | 3,184,847             | A   | 5/1965  | Rosen              |   |         |                    |  |
|      | 3,482,895             | A   | 12/1969 | Becklin            |   |         |                    |  |
|      | 3,521,216             | A   | 7/1970  | Jerair             |   |         |                    |  |
|      | 3,590,988             | A   | 7/1971  | Douglass           |   |         |                    |  |
|      | 3,665,991             | A   | 5/1972  | Gillemot et al.    |   |         |                    |  |
|      | 3,689,866             | A   | 9/1972  | William            |   |         |                    |  |
|      | 3,832,725             | A   | 8/1974  | Cook               |   |         |                    |  |
|      | 3,922,477             | A   | 11/1975 | Glowacz            |   |         |                    |  |
|      | 4,097,878             | A   | 6/1978  | Cramer             |   |         |                    |  |
|      | 4,298,204             | A   | 11/1981 | Jinkins            |   |         |                    |  |
|      | 4,312,580             | A   | 1/1982  | Schwomma et al.    |   |         |                    |  |
|      | 4,335,930             | A   | 6/1982  | Feldman            |   |         |                    |  |
|      | 4,352,968             | A   | 10/1982 | Pounds             |   |         |                    |  |
|      | 4,375,323             | A   | 3/1983  | Inagaki et al.     |   |         |                    |  |
|      | 4,383,743             | A   | 5/1983  | Nozawa et al.      |   |         |                    |  |
|      | 4,418,830             | A   | 12/1983 | Dzung et al.       |   |         |                    |  |
|      | 4,420,078             | A   | 12/1983 | Belt et al.        |   |         |                    |  |
|      | 4,440,464             | A   | 4/1984  | Spinner            |   |         |                    |  |
|      | 4,546,874             | A   | 10/1985 | Kirchhan           |   |         |                    |  |
|      | 4,584,718             | A   | 4/1986  | Fuller             |   |         |                    |  |
|      | 4,649,453             | A   | 3/1987  | Iwasawa            |   |         |                    |  |
|      | 4,658,956             | A   | 4/1987  | Takeda et al.      |   |         |                    |  |
|      | 4,683,587             | A   | 7/1987  | Silverman          |   |         |                    |  |
|      | 4,686,332             | A   | 8/1987  | Greanias et al.    |   |         |                    |  |
|      | 4,703,161             | A   | 10/1987 | McLean             |   |         |                    |  |
|      | 4,712,657             | A   | 12/1987 | Myers et al.       |   |         |                    |  |
|      | 4,733,776             | A   | 3/1988  | Ward               |   |         |                    |  |
|      | 4,762,227             | A   | 8/1988  | Patterson          |   |         |                    |  |
|      | 4,803,504             | A   | 2/1989  | Maeno et al.       |   |         |                    |  |
|      | 4,836,256             | A   | 6/1989  | Meliconi           |   |         |                    |  |
|      | 4,942,514             | A   | 7/1990  | Miyagaki et al.    |   |         |                    |  |
|      | 4,963,902             | A   | 10/1990 | Fukahori           |   |         |                    |  |
|      | 4,977,483             | A   | 12/1990 | Perretta           |   |         |                    |  |
|      | 4,994,829             | A   | 2/1991  | Tsukamoto          |   |         |                    |  |
|      | 5,002,184             | A   | 3/1991  | Lloyd              |   |         |                    |  |
|      | 5,025,921             | A   | 6/1991  | Gasparaitis et al. |   |         |                    |  |
|      | 5,087,934             | A   | 2/1992  | Johnson            |   |         |                    |  |
|      | 5,092,458             | A   | 3/1992  | Yokoyama           |   |         |                    |  |

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,634,494 B1	10/2003	Derr et al.	7,366,555 B2	4/2008	Jokinen et al.
6,636,697 B2	10/2003	Smith et al.	7,369,881 B2	5/2008	Tsujimoto
6,646,864 B2	11/2003	Richardson	7,389,869 B2	6/2008	Mason
6,659,274 B2	12/2003	Enners	7,400,917 B2	7/2008	Wood et al.
6,665,174 B1	12/2003	Derr et al.	7,409,148 B2	8/2008	Takahashi et al.
6,667,738 B2	12/2003	Murphy	7,418,278 B2	8/2008	Eriksson et al.
6,669,017 B2	12/2003	Linihan	7,428,427 B2	9/2008	Brunstrom et al.
6,698,608 B2	3/2004	Parker et al.	7,436,653 B2	10/2008	Yang et al.
6,701,159 B1	3/2004	Powell	7,448,908 B2	11/2008	Iwahori et al.
6,721,651 B1	4/2004	Minelli	7,449,650 B2	11/2008	Richardson et al.
6,731,913 B2	5/2004	Humphreys et al.	7,464,813 B2	12/2008	Carnevali
6,739,759 B1	5/2004	Seeley	7,464,814 B2	12/2008	Carnevali
6,751,552 B1	6/2004	Minelli	7,495,659 B2	2/2009	Marriott et al.
6,760,570 B1	7/2004	Higdon	7,495,895 B2	2/2009	Carnevali
6,772,899 B2	8/2004	Delmon	7,499,040 B2	3/2009	Zadesky et al.
6,778,388 B1	8/2004	Minelli	7,502,550 B2	3/2009	Ariga
6,781,825 B2	8/2004	Shih et al.	7,511,956 B2	3/2009	Tomioaka et al.
6,785,566 B1	8/2004	Irizarry	7,525,792 B2	4/2009	Yokote
6,819,549 B1	11/2004	Lammers-Meis et al.	7,535,799 B2	5/2009	Polany et al.
6,819,866 B2	11/2004	Silva	7,540,844 B2	6/2009	Muser
6,822,161 B2	11/2004	Komatsu et al.	7,555,325 B2	6/2009	Goros
6,822,640 B2	11/2004	Derocher	7,558,594 B2	7/2009	Wilson
6,839,430 B2	1/2005	Kwak	7,594,576 B2	9/2009	Chen et al.
6,844,845 B1	1/2005	Whiteside et al.	7,609,512 B2	10/2009	Richardson et al.
6,848,930 B2	2/2005	Fukuda	7,613,386 B2	11/2009	Shimamura
6,913,201 B1	7/2005	Wagner et al.	7,623,898 B2	11/2009	Holmberg
6,914,774 B1	7/2005	Albertini et al.	7,630,746 B2	12/2009	Holmberg
6,929,141 B1	8/2005	Minghetti	7,653,292 B2	1/2010	Yamaguchi et al.
6,953,126 B2	10/2005	Parker et al.	7,663,878 B2	2/2010	Swan et al.
6,954,405 B2	10/2005	Polany et al.	7,663,879 B2	2/2010	Richardson et al.
6,955,293 B1	10/2005	Katsanevas	7,668,580 B2	2/2010	Shin et al.
6,962,454 B1	11/2005	Costello	7,679,674 B2	3/2010	Nishizawa
6,971,517 B2	12/2005	Chen	7,688,580 B2	3/2010	Richardson et al.
6,975,888 B2	12/2005	Buesseler et al.	7,697,269 B2	4/2010	Yang et al.
6,980,777 B2	12/2005	Shepherd et al.	7,711,400 B2	5/2010	Nuovo
6,983,130 B2	1/2006	Chien et al.	7,733,642 B2	6/2010	Liou et al.
6,987,527 B2	1/2006	Kossin	7,755,975 B2	7/2010	Pettersen et al.
6,992,659 B2	1/2006	Gettemy	7,772,507 B2	8/2010	Orr et al.
6,995,976 B2	2/2006	Richardson	7,775,354 B2	8/2010	Latchford et al.
7,025,274 B2	4/2006	Solomon et al.	7,787,756 B2	8/2010	Funahashi et al.
7,033,215 B2	4/2006	Kobayashi	7,789,228 B2	9/2010	Zenzai
7,046,230 B2	5/2006	Zadesky et al.	7,789,696 B2	9/2010	Umei et al.
7,048,561 B1	5/2006	Elbaz	7,801,425 B2	9/2010	Fantone et al.
7,050,712 B2	5/2006	Shimamura	7,854,434 B2	12/2010	Heiman et al.
7,050,841 B1	5/2006	Onda	7,889,489 B2	2/2011	Richardson et al.
7,054,441 B2	5/2006	Pletikosa	7,907,394 B2	3/2011	Richardson et al.
7,061,762 B2	6/2006	Canova et al.	7,926,818 B2	4/2011	Isono
7,069,063 B2	6/2006	Halkosaari et al.	7,933,122 B2	4/2011	Richardson et al.
7,072,467 B2	7/2006	Ono	7,936,566 B2	5/2011	Shigyo et al.
7,074,066 B2*	7/2006	Pepe .....	7,941,196 B2	5/2011	Kawasaki et al.
		G02B 6/3807	7,944,697 B2	5/2011	Hata et al.
		439/271	7,975,870 B2	7/2011	Laule et al.
7,082,264 B2	7/2006	Watanabe et al.	7,978,092 B2	7/2011	Osaka
7,085,542 B2	8/2006	Dietrich et al.	7,988,468 B2	8/2011	Yang et al.
7,089,547 B2	8/2006	Goodman et al.	7,988,476 B2*	8/2011	Billman .....
7,106,959 B2	9/2006	Sato			H01R 13/622
7,146,701 B2	12/2006	Mahoney et al.	8,014,134 B2	9/2011	439/271
7,158,376 B2	1/2007	Richardson et al.	8,024,015 B2	9/2011	Liu et al.
7,180,735 B2	2/2007	Thomas et al.	8,031,472 B2	10/2011	Araki et al.
7,194,086 B2	3/2007	Pletikosa	8,032,194 B2	10/2011	Bicket et al.
7,194,202 B2	3/2007	Funahashi et al.	8,050,022 B2	11/2011	Liu et al.
7,194,291 B2	3/2007	Peng	8,053,668 B2	11/2011	McIntyre
7,225,923 B2	6/2007	Hallee et al.	8,068,331 B2	11/2011	Lai et al.
7,230,823 B2	6/2007	Richardson et al.	8,089,757 B2	1/2012	Sauers et al.
7,236,588 B2	6/2007	Gartrell	8,101,859 B2	1/2012	Chen et al.
7,255,228 B2	8/2007	Kim	8,138,434 B2	1/2012	Zadesky
7,263,032 B2	8/2007	Polany et al.	8,164,899 B2	3/2012	Tang et al.
7,290,654 B2	11/2007	Hodges	8,167,126 B2	4/2012	Yamaguchi et al.
7,303,418 B2	12/2007	O'Connor	8,191,706 B1	5/2012	Stiehl
7,312,984 B2	12/2007	Richardson et al.	8,204,561 B2	6/2012	Liu
7,327,841 B2	2/2008	Schreiber et al.	8,210,859 B2	6/2012	Mongan et al.
7,341,144 B2	3/2008	Tajiri et al.	8,223,997 B2	7/2012	Tiberghien et al.
7,343,184 B2	3/2008	Rostami	8,251,210 B2	7/2012	Wilson, II et al.
7,352,961 B2	4/2008	Watanabe et al.	8,265,264 B2	8/2012	Schmidt et al.
7,362,570 B2	4/2008	Su	8,269,104 B2	9/2012	Yamaguchi et al.
7,365,281 B2	4/2008	Yamaguchi et al.	8,286,789 B2	9/2012	Choraku et al.
			8,311,595 B2	10/2012	Wilson et al.
			8,342,325 B2	11/2012	Takatsuka et al.
			8,373,980 B2	1/2013	Rayner
				2/2013	Reber

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,393,466	B2	3/2013	Rayner	2007/0241012	A1	10/2007	Latchford et al.
8,400,408	B2	3/2013	Hotelling et al.	2007/0261976	A1	11/2007	Anderson
8,430,240	B2	4/2013	Kim	2007/0261978	A1	11/2007	Sanderson
8,454,101	B2	6/2013	Kuo	2007/0280053	A1	12/2007	Polany et al.
8,531,824	B2	9/2013	Rayner	2007/0297149	A1	12/2007	Richardson et al.
8,531,834	B2	9/2013	Rayner	2008/0039161	A1	2/2008	Chan
8,548,541	B2	10/2013	Rayner	2008/0055258	A1	3/2008	Sauers
8,564,950	B2	10/2013	Rayner	2008/0081679	A1	4/2008	Kawasaki et al.
8,570,737	B2	10/2013	Rayner	2008/0157485	A1	7/2008	Isono
8,611,969	B2	12/2013	Smith et al.	2008/0163463	A1	7/2008	Hulden
8,708,142	B2	4/2014	Rayner	2008/0164267	A1	7/2008	Huber
2001/0040109	A1	11/2001	Yaski et al.	2008/0171456	A1	7/2008	Vanzo
2002/0003584	A1	1/2002	Kossin	2008/0316687	A1	12/2008	Richardson et al.
2002/0009195	A1	1/2002	Schon	2009/0009945	A1	1/2009	Johnson et al.
2002/0065054	A1	5/2002	Humphreys et al.	2009/0017884	A1	1/2009	Rotschild
2002/0071550	A1	6/2002	Pletikosa	2009/0028535	A1	1/2009	Funahashi et al.
2002/0079244	A1	6/2002	Kwong	2009/0032420	A1	2/2009	Zenzai
2002/0085342	A1	7/2002	Chen et al.	2009/0034169	A1	2/2009	Richardson et al.
2002/0085709	A1	7/2002	Hsu	2009/0080153	A1	3/2009	Richardson et al.
2002/0086702	A1	7/2002	Lai et al.	2009/0087655	A1	4/2009	Yamada et al.
2002/0090212	A1	7/2002	Shimamura et al.	2009/0090532	A1	4/2009	Lai et al.
2002/0101707	A1	8/2002	Canova et al.	2009/0109635	A1	4/2009	Chen et al.
2002/0122353	A1	9/2002	Polany et al.	2009/0111543	A1	4/2009	Tai et al.
2002/0136557	A1	9/2002	Shimamura	2009/0113758	A1	5/2009	Nishiwaki et al.
2002/0137475	A1	9/2002	Shou et al.	2009/0117957	A1	5/2009	Araki et al.
2002/0175096	A1	11/2002	Linihan	2009/0167545	A1	7/2009	Osaka
2002/0175901	A1	11/2002	Gettemy	2009/0211775	A1	8/2009	Yamaguchi et al.
2002/0193136	A1	12/2002	Halkosaari et al.	2009/0215412	A1	8/2009	Liu et al.
2002/0195910	A1	12/2002	Hus et al.	2009/0260844	A1	10/2009	Tseng
2003/0080947	A1	5/2003	Genest et al.	2009/0283184	A1	11/2009	Han
2003/0095374	A1	5/2003	Richardson	2010/0044198	A1	2/2010	Tang et al.
2003/0103624	A1	6/2003	Hu	2010/0053355	A1	3/2010	Iwase et al.
2003/0111366	A1	6/2003	Enners	2010/0085691	A1	4/2010	Yeh et al.
2003/0118332	A1	6/2003	Smith et al.	2010/0093412	A1	4/2010	Serra et al.
2003/0118334	A1	6/2003	Smith et al.	2010/0096284	A1	4/2010	Bau
2003/0128397	A1	7/2003	Smith et al.	2010/0104814	A1	4/2010	Richardson et al.
2003/0151890	A1	8/2003	Huang et al.	2010/0144194	A1	6/2010	Umei et al.
2003/0223577	A1	12/2003	Ono	2010/0147737	A1	6/2010	Richardson et al.
2004/0014506	A1	1/2004	Kemppinen	2010/0181108	A1	7/2010	Hata et al.
2004/0076415	A1	4/2004	Silva	2010/0203931	A1	8/2010	Hyneczek et al.
2004/0089570	A1	5/2004	Chien et al.	2010/0206601	A1	8/2010	Choraku et al.
2004/0120219	A1	6/2004	Polany et al.	2010/0238119	A1	9/2010	Dubrovsky et al.
2004/0121226	A1	6/2004	Kaelin et al.	2010/0313485	A1	12/2010	Kuo
2004/0188120	A1	9/2004	Komatsu et al.	2011/0017620	A1	1/2011	Latchford et al.
2004/0195783	A1	10/2004	Akagi et al.	2011/0024315	A1	2/2011	Kim
2004/0203502	A1	10/2004	Dietrich et al.	2011/0073608	A1	3/2011	Richardson et al.
2004/0226836	A1	11/2004	Schreiber et al.	2011/0157055	A1	6/2011	Tilley et al.
2005/0052425	A1	3/2005	Zadesky et al.	2011/0157800	A1	6/2011	Richardson et al.
2005/0110768	A1	5/2005	Marriott et al.	2011/0228460	A1	9/2011	Kim et al.
2005/0115852	A1	6/2005	Funahashi et al.	2011/0300730	A1	12/2011	Someya
2005/0123161	A1	6/2005	Polany et al.	2011/0300731	A1	12/2011	Nakamura
2005/0139498	A1	6/2005	Goros	2012/0031914	A1	2/2012	Liu
2005/0167304	A1	8/2005	Shimamura	2012/0043235	A1	2/2012	Klement
2005/0174727	A1	8/2005	Thomas et al.	2012/0099261	A1	4/2012	Reber
2005/0181843	A1	8/2005	Tsujimoto	2012/0099262	A1	4/2012	Reber et al.
2005/0224508	A1	10/2005	Tajiri et al.	2012/0099265	A1	4/2012	Reber
2005/0247584	A1	11/2005	Lu	2012/0099266	A1	4/2012	Reber et al.
2005/0279661	A1	12/2005	Hodges	2012/0100737	A1	4/2012	Frey
2006/0008261	A1	1/2006	Watanabe et al.	2012/0103844	A1	5/2012	Piedra et al.
2006/0110146	A1	5/2006	Ariga	2012/0118773	A1	5/2012	Rayner
2006/0255493	A1	11/2006	Fouladpour	2012/0168336	A1	7/2012	Schmidt et al.
2006/0274493	A1	12/2006	Richardson et al.	2012/0196464	A1	8/2012	Lu
2006/0279924	A1	12/2006	Richardson et al.	2012/0211382	A1	8/2012	Rayner
2007/0040931	A1	2/2007	Nishizawa	2012/0314354	A1	12/2012	Rayner
2007/0071423	A1	3/2007	Fantone et al.	2013/0027862	A1	1/2013	Rayner
2007/0074473	A1	4/2007	Yamaguchi et al.	2013/0043777	A1	2/2013	Rayner
2007/0086273	A1	4/2007	Polany et al.	2013/0077226	A1	3/2013	Rayner
2007/0109730	A1	5/2007	Shigyo et al.	2013/0084728	A1	4/2013	Omae et al.
2007/0110416	A1	5/2007	Yamaguchi et al.	2013/0088130	A1	4/2013	Rayner
2007/0115387	A1	5/2007	Ho	2013/0092576	A1	4/2013	Rayner
2007/0138920	A1	6/2007	Austin et al.	2013/0182881	A1	7/2013	Horino et al.
2007/0139873	A1	6/2007	Thomas et al.	2013/0203277	A1*	8/2013	Gaubert
2007/0146985	A1	6/2007	Mick et al.				..... H01R 13/5219
2007/0158220	A1	7/2007	Cleereman et al.	2013/0220841	A1	8/2013	Yang
2007/0215663	A1	9/2007	Chongson et al.	2013/0224993	A1	8/2013	Purdy
				2013/0334072	A1	12/2013	Rayner
				2014/0038443	A1	2/2014	Campbell et al.

(56)

**References Cited**

U.S. PATENT DOCUMENTS

2014/0213088 A1 7/2014 Furuya et al.  
2014/0248787 A1 9/2014 Suzuki et al.

FOREIGN PATENT DOCUMENTS

JP	H0561069	U	8/1993
JP	H0818637	A	6/1994
JP	3060175	U	7/1999
JP	2000125916	A	5/2000
JP	2000341383	A	12/2000
JP	2002280757	A	9/2002
JP	2003164316	A	6/2003
WO	1994000037	A1	1/1994
WO	1999041958	A1	8/1999
WO	2000051315	A1	8/2000
WO	2002011161	A2	2/2002
WO	2007122722	A1	11/2007
WO	2012074151	A1	6/2012
WO	2012051358		12/2012
WO	2012174175	A2	12/2012
WO	2013096927	A1	6/2013

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E






FIG. 2A




FIG. 2B




FIG. 2C






FIG. 2E




FIG. 2F




FIG. 2G




FIG. 2H




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B






FIG. 7A




FIG. 7B

1

## CONNECTOR FOR FLUIDLY SEALING AN APERTURE OF A PROTECTIVE CASE

This disclosure relates generally to cases, covers, shells, and enclosures for electronic devices.

### BACKGROUND

Portable electronic devices are commonly used for communication, data processing, entertainment, and/or information gathering purposes, and are commonly used in a variety of environments. Portable electronic devices include devices such as smartphones, cellular phones, mobile communication devices, computers, portable computing devices, mobile computing devices, tablet computers, cameras, video players, audio players, electronic media readers, two-way radios, satellite-based navigation devices (e.g. global positioning system receiving device), and/or other types of electronic computing or communication devices, including combinations thereof. Such devices can have ports or female connectors that allow a wired connection that permits data and/or power transmission between the device and another device or accessory, such as a battery, a headphone and/or a microphone.

It is desirable to use such portable electronic devices in environments that pose potential risk of damage to the device from environmental contaminants such as dirt, dust, water, liquid, etc. In such instances, use of a water-resistant or waterproof case for the portable electronic device is desirable to protect the portable electronic device from the possible environmental contaminants is desirable. Such waterproof or water-resistant case may include a port that can be opened to provide access to a connector of the encased portable electronic device; the port can then be closed to provide a waterproof or water-resistant seal at the port.

However, in certain instances it is desirable to maintain a removable wired connection to the portable electronic device inside a case, while still maintaining the water-resistant or waterproof integrity of the case. For example, while exercising or walking outdoors a user may use a smartphone to listen to music through a set of wired headphones, or a user may charge the smartphone using a separate battery pack via a wired connection.

The case that protects the portable electronic device has a thickness that creates additional distance which must be crossed by a removable wired connector (e.g. a male headphone plug and/or male power plug). Using a standard connector with such a case can be accommodated by an aperture that allows the backshell of the connector to cross at least part of the case thickness. However, once the removable wired connector is inserted, a leak path is introduced between the wired connector and the corresponding device connector.

In some instances, a water-resistant or waterproof connection between the case, the removable wired connector, and the device connector can be made using an intermediary adaptor with a longer-than-normal male portion and having a body that can be secured to the case (e.g. by threads or a bayonet-style connection). Such an adaptor may include a seal that interfaces with a portion of the case once the adaptor is secured to the case. However, such intermediary adaptors may be easily misplaced by users.

This disclosure is directed to cases, shells, and housings that permit a user to form a removable water-resistant or waterproof seal between a connector and a water-resistant or waterproof case, while still allowing the connector to con-

2

nect with the portable electronic device and transmit data and/or power between the encased portable electronic device and the connector.

### SUMMARY

In one aspect, cases, shells, and housings for a portable electronic device are disclosed, the portable electronic device having a device connector for transmission of data and/or power between the device connector and a data and/or power source via a reciprocal connector assembly. Cases, shells, and housings described herein include an aperture disposed proximate the device connector of the installed portable electronic device. The aperture passes between an outer surface and an inner surface of the case and is defined by a surface between the outer and inner surfaces. The aperture also has a circumference. A compliant seal is disposed on the surface of the aperture and around the circumference of the aperture. The compliant seal interfaces with at least a portion of a backshell of the reciprocal connector assembly when the reciprocal connector assembly is inserted through the aperture to interface with the device connector of the installed portable electronic device.

In another aspect, cases, shells, and housings for a portable electronic device are disclosed, with the portable electronic device having a device connector for transmission of data and/or power between the device connector and a data and/or power source via a reciprocal connector assembly. In such an aspect, an aperture is disposed proximate the device connector of the installed portable electronic device, with the aperture passing between an outer surface and an inner surface of the case. The aperture has a circumference. A compliant seal is disposed on the outer surface of the case and surrounding the circumference of the aperture. The compliant seal interfaces with a face portion of a backshell portion of the reciprocal connector assembly when the reciprocal connector assembly is inserted through the aperture to interface with the device connector of the installed portable electronic device.

In another aspect, a connector for connecting a reciprocal connector to a device connector of a portable electronic device accessed through an aperture of a protective case is provided. The connector includes a sleeve for receiving at least a portion of the reciprocal connector; an orientation member including a hollow body member configured to receive at least a portion of the reciprocal connector, the orientation member including one or more depth arms configured to contact a face portion of the reciprocal connector and resist movement of the reciprocal connector in a first direction; and a seal positioned between the sleeve and the device connector, the seal fluidly sealing the aperture of the protective case.

In another aspect, a connector for positioning a reciprocal connector in a predetermined position is provided. The connector includes a hollow body member having an interior configured to receive at least a portion of the reciprocal connector within the interior; one or more depth arms extending from the hollow body member, the depth arms configured to contact a face portion of the reciprocal connector and resist movement of the reciprocal connector in a first direction; a first pair of aligning tabs configured to contact a first portion of the reciprocal connector when the reciprocal connector is received in the interior, the first pair of aligning tabs further configured to center and hold the first portion of the reciprocal connector along a first axis within the interior of the hollow body member; and a second pair of aligning tabs configured to contact a second portion of the

reciprocal connector when the reciprocal connector is received in the interior, the second pair of aligning tabs further configured to center and hold the second portion of the reciprocal connector along a second axis within the interior of the hollow body member.

The summary of the invention described above is non-limiting and other features and advantages of the invention will be apparent from the following detailed description of the invention, and from the claims.

### BRIEF DESCRIPTION OF THE FIGURES

FIG. 1A shows a perspective view of a protective case encasing a portable electronic device, and a connector for connecting with the portable electronic device.

FIG. 1B shows a close-up perspective view of the case of FIG. 1A with a reciprocal connector assembly inserted through an aperture of the case.

FIG. 1C shows a side sectional view of part of the case of FIG. 1A and including an aperture seal on the interior surface of the case aperture.

FIG. 1D shows a side sectional view of part of the case of FIG. 1A, also including a different type of aperture seal on the interior surface of the case aperture.

FIG. 1E shows a side sectional view of a portion of the case of FIG. 1A, utilizing a different type of aperture seal on a face portion of the case.

FIG. 2A shows a perspective view of a front of a connector for sealing a port of a portable electronic device.

FIG. 2B shows a perspective view of the rear of the connector of FIG. 2A.

FIG. 2C shows a sectional view of the connector of FIG. 2A.

FIG. 2D shows an exploded view of the connector of FIG. 2A, an electronic device, and a reciprocal connector.

FIG. 2E shows the connector of FIG. 2A in an open configuration.

FIG. 2F shows a sectional view of the lower portion of the connector of FIG. 2E.

FIG. 2G shows the connector of FIG. 2A in the open configuration with the reciprocal connector installed.

FIG. 2H shows a sectional view of the connector and reciprocal connector attached to a port of the electronic device.

FIG. 3A shows an exemplary seal, receiving member, and orientation member of the connector of FIG. 2A.

FIG. 3B shows an end view of the receiving member, and orientation member of FIG. 3A.

FIG. 4 shows a perspective view of an exemplary orientation member of the connector of FIG. 2A.

FIG. 5A shows a perspective view of another exemplary orientation member of the connector of FIG. 2A.

FIG. 5B shows a sectional view of the exemplary orientation member of FIG. 5A.

FIG. 5C shows a side view of the exemplary orientation member of FIG. 5A.

FIG. 6A shows a perspective view of still another exemplary orientation member of the connector of FIG. 2A.

FIG. 6B shows a side view of the exemplary orientation member of FIG. 6A.

FIG. 7A shows a sectional view of an exemplary port of a portable electronic device for receiving a connector including the orientation member of FIG. 4.

FIG. 7B shows a sectional view of another exemplary port of a portable electronic device receiving the orientation member of FIG. 6A.

### DETAILED DESCRIPTION OF THE DISCLOSURE

The present disclosure is directed to cases, covers, shells, and enclosures for electronic devices. The cases, covers, shells, and enclosures have an aperture or port that allows connector access to a data and/or power connector (e.g. male or female) on the housing of the electronic device itself. An aperture seal formed from a compliant material is disposed on a surface of the aperture or port. A data and/or power connector for an accessory (e.g. headphones and/or battery) that is inserted through the aperture of the case forms a water-resistant or waterproof seal with the aperture seal, eliminating the need for a separate intermediary adaptor that secures to and seals with the case.

FIG. 1A shows a perspective view of a case 110 encasing a portable electronic device 100. Aperture 120 of case 110 is positioned proximate device connector 102 of portable electronic device 100. Case 110 is waterproof or water-resistant when a door or cover (not shown) covers aperture 120. Such waterproof and water-resistant doors and covers may include those described in U.S. Pat. Pub. No. 2012/0211382, incorporated herein by reference. Reciprocal connector assembly 140 is also shown, positioned to be inserted through aperture 120 such that reciprocal connector assembly 140 can interface with device connector 102.

Reciprocal connector assembly 140 allows for an electrical connection to device connector 102 of portable electronic device 100. In some exemplary embodiments, reciprocal connector assembly 140 provides an electronic path for interacting with portable electronic device 100. In some exemplary embodiments, reciprocal connector assembly 140 includes a cable 148 that terminates in another connector (e.g. a USB connector such as type-A or type-B), a wall adapter (e.g. for plugging into an outlet for charging), or terminates at an accessory device (e.g. a set of headphones or a battery); in other instances, backshell 144 may be connected to a rigid or semi-rigid accessory, without an intervening cable. In some exemplary embodiments, reciprocal connector assembly 140 terminates in an adapter (not shown) to which a cable or accessory may be removably connected.

Reciprocal connector assembly 140 includes backshell 144 and reciprocal connector 142 (depicted here as a male component). In other exemplary embodiments, reciprocal connector 142 may be a female component configured to receive a corresponding male component device connector 102 of portable electronic device 100. Reciprocal connector assembly illustratively includes a plurality of wires, electronic conductors, and electrical components. In some exemplary embodiments, reciprocal connector 142 is a connector carrying a digital signal, such as a 30 pin dock connector, an 8-pin connector, a USB type-A connector, a USB Micro-A type connector, a USB Mini-A type connector, a USB type-B connector, a USB Micro-B type connector, a USB Mini-B type connector, a USB type-C connector, or another suitable connector.

FIG. 1B shows a close-up perspective view of case 110 with reciprocal connector assembly 140 inserted through aperture 120 and into device connector 102 (not visible in FIG. 1B) of portable electronic device 100. Aperture 120 has a circumference intentionally larger than that of backshell 144 in order to accommodate a variety of backshell sizes, as the backshell may not have highly constrained tolerance. Due to the larger circumference, a potential leak path or gap 123 is visible between backshell 144 and aperture 120. This gap allows liquid to leak from outside case 110, though

aperture 120, into case 110, and between backshell 144 and device connector 102 (not visible in FIG. 1B). In order to block this leak path 123, an aperture seal may be added to aperture 120 that interfaces with a portion of backshell 144 to seal aperture 120 when reciprocal connector assembly 140 is inserted.

FIG. 1C illustrates a side sectional view of part of case 110 described above, also including an aperture seal 130a on interior surface 122 of aperture 120. Aperture seal 130a is configured as a gland seal, and is disposed around the circumference of aperture 120. Reciprocal connector assembly 140 is inserted through aperture 120, with reciprocal connector 142 inserted into device connector 102 and backshell 144 partially disposed in aperture 120 and interfacing with aperture seal 130a. The sealed interface between backshell 144 and interior surface 122 of case 110 fluidly seals aperture 120 around device connector 102, providing for a waterproof connection between device connector 102 of portable electronic device 100 and reciprocal connector 142 of reciprocal connector assembly 140.

FIG. 1D shows a side sectional view of part of case 110 described above, including a different style of aperture seal 130b on interior surface 122 of aperture 120. Aperture seal 130b is configured with a plurality of ridges 132a-c that provide additional surface area for sealing with backshell 144.

FIG. 1E illustrates a side sectional view of a portion of case 110, utilizing an aperture seal 130c that is configured as a face seal. Aperture seal 130c is disposed proximate the face portion 124 of aperture 120, and interfaces with a corresponding face portion 146 of backshell 144 to form a water-resistant or waterproof seal. In some embodiments, aperture seal 130c may interact with a removable door or cover having a sealing seat that interfaces with aperture seal 130c to seal aperture 120 when the removable door or cover is closed against aperture 120. The door or cover may include latching mechanisms or catches on both the door and the outer surface of the case that removably interact to maintain the seal between the sealing seat and the aperture seal 130c. The door or cover may be completely removable and separate from the case, or it may be attached by a tether, a hinge, or other attachment element. The door or cover may slide along a surface of the case along rails on the exterior of the case. Exemplary doors and covers are found in U.S. Pat. Nos. 2012/0211382, 2012/0314354, and 2015/0201723 each of which is incorporated herein by reference.

Other seal configurations may be utilized on the interior surface 122 or face portion 124 of aperture 120, including but not limited to: gland seals (male or female); boss seal; lip seal; stuffing box/gland; labyrinth seals; and connectors manufactured by MARSH & MARINE.

FIG. 2A-2H illustrate a sealing connector 200 for sealing an aperture 120 of case 110. FIG. 2A shows a perspective view of a front the sealing connector 200. FIG. 2C shows a cross-sectional view of the sealing connector 200. FIG. 2D shows an exploded view of the sealing connector 200, case 110, and reciprocal connector assembly 140. FIG. 2E shows the sealing connector 200 in an open configuration. FIG. 2F shows a sectional view of the lower portion of the sealing connector 200. FIG. 2G shows the sealing connector 200 in an open configuration with the reciprocal connector assembly 140 positioned in an interior of connector assembly 200. FIG. 2H shows a sectional view of the sealing connector 200 and reciprocal connector assembly 140 attached to the electronic device 100.

Sealing connector 200 includes sleeve 210. Sleeve 210 has in interior cavity 218, a first opening 220 at a first end

of sealing connector 200 and a second opening 222 opposite the first opening at a second end of the sealing connector. Sleeve 210 includes a living hinge 212 along one side of sleeve 210, allowing sleeve 210 to move between a closed configuration, as illustrated in FIGS. 2A and 2B, and an open configuration, as illustrated in FIGS. 2E and 2G. A latch 214 is seated against a corresponding interface 216 to secure the sleeve 210 in the closed configuration. Latch 214 and sleeve 210 are illustratively formed from a resilient material, such as a plastic, that allow the end of latch 214 to flex away from the interface 216, allowing sleeve 210 to move from the closed configuration to the open configuration.

Sealing connector 200 includes a gasket 230 for sealing an interior of sealing connector 200. Gasket 230 is illustratively positioned at least partially in interior cavity 218 of sealing connector 210. Gasket 230 includes an upper portion 232 and a lower portion 234, which in some exemplary embodiments are flexibly connected by living hinge 235. In other exemplary embodiments, upper portion 232 and lower portion 234 are not directly connected.

Gasket 230 includes an interior cavity 236, a first opening 238 proximate first opening 220 of the sleeve 210, and second opening 240 proximate the second opening 222 of the sleeve 210. Interior cavity 236 is configured to receive at least a portion of reciprocal connector assembly 140 as described in more detail below. First opening 238 includes a plurality of resilient ridges 242 configured to contact a cable 148 of reciprocal connector assembly 140 to fluidly seal the first opening 238. Second opening 240 includes a plurality of resilient ridges 244 configured to contact corresponding channels 262 of receiver 260 to fluidly seal the second opening 236. Gasket 230 illustratively includes O-ring 246. In some exemplary embodiments, O-ring 246 is formed as part of gasket 230. In other embodiments, O-ring 246 is not directly attached to gasket 230. O-ring 246 is illustratively received into O-ring channel 264 of receiver 260. O-ring 246 is configured to contact a wall of sleeve 210 to fluidly seal the second opening 222 of sleeve 210.

Sealing connector 200 includes a seal 250. Seal 250 is attached to front face 266 of receiver 260 with a suitable adhesive. As illustrated in FIG. 2H, seal 250 interfaces with the receiver 260 and case 110 to fluidly seal the aperture 120 containing device connector 102. In this way, reciprocal connector assembly 140 can be provided with a waterproof connection to device connector 102 of portable electronic device 100, and can be used to, for example, charge electronic device 100 or exchange data electronically with electronic device 100.

Referring next to FIG. 3A, an exemplary seal 250, receiver 260, and orientation member 280 are illustrated. FIG. 3B illustrates an end view of receiver 260 and orientation member 280.

Sealing connector 200 includes receiver 260. Receiver 260 includes channels 262 for receiving resilient ridges 244 of gasket 230 and O-ring channel 264 for receiving O-ring 246. Receiver 260 further includes front face 266 onto which seal 250 is adhered. An interior 268 of receiver 260 is configured to receive at least a portion of orientation member 280. Interior 268 further includes a plurality of ridges 270 configured to receiving locking tabs 288 of orientation member 280.

FIG. 4 shows a perspective view of an exemplary orientation member 280 of the connector of FIG. 2A. Orientation member 280 is positioned in receiver 260 and held in place by a plurality of locking tabs 290 that snap behind ridges 270 of receiver 260.

Orientation member **280** illustratively includes a hollow body member **282** for receiving at least a portion of reciprocal connector assembly **140** and orienting reciprocal connector **142** such that it can be inserted through aperture **120** into device connector **102** of portable electronic device **100**. In the exemplary embodiment illustrated in FIG. 4, the hollow body member **282** has a substantially rectangular cross-section.

The depth of insertion of the reciprocal connector assembly **140** is limited a pair of L-shaped depth arms **284**. When reciprocal connector assembly **140** is fully inserted into orientation member **280**, depth arms **284** contact a face portion **146** of backshell **144** and prevent further forward movement of backshell **144**.

Orientation member **280** further includes first aligning tabs **286** and second aligning tabs **288**, each formed from a resilient material such as a metal. As the reciprocal connector assembly **140** is inserted into orientation member **280**, first alignment tabs **286** contact a first pair of opposing sides of backshell **144** and second alignment tabs **288** contact a second pair of opposing sides of backshell **144**. First alignment tabs are configured to center and hold backshell **144** along a first axis within orientation member **280** and second alignment tabs are configured to center and hold backshell **144** along a second axis within orientation member **280**.

FIG. 5A shows a perspective view of another exemplary orientation member **292**. In some exemplary embodiments, connector **200** includes orientation member **292** in place of orientation member **280**. Orientation member **292** is similar to orientation member **280** as illustrated in FIG. 4 and similar parts are indicated with similar reference numbers. FIG. 5B shows a sectional view of orientation member **292**. FIG. 5C shows a side view of orientation member **292**. In the exemplary embodiment illustrated in FIGS. 5A-5C, the hollow body member **282** has a substantially rectangular cross-section.

Orientation member **292** includes attachment tabs **294** extending from hollow body member **282** each formed from a resilient material such as a metal. Each attachment tab **294** terminates in an attachment end **296**. As illustrated in FIG. 7B, each attachment end **296** is configured to be received within a corresponding receiving slot **124** in the interior surface **122** of aperture **120** and removably secure orientation member **292** to case **110**.

FIG. 6A shows a perspective view of still another exemplary orientation member **298** of the connector **200** of FIG. 2A. In some exemplary embodiments, connector **200** includes orientation member **298** in place of orientation member **280**. Orientation member **298** is similar to orientation member **280** as illustrated in FIG. 4 and to orientation member **292** as illustrated in FIGS. 5A-5C and orientation. FIG. 6B shows a side view of the orientation member **298**. Similar parts are indicated with similar reference numbers. In the exemplary embodiment illustrated in FIGS. 6A and 6B, the hollow body member **282** has a cross-section with substantially rounded edges.

FIG. 7A shows a sectional view of an exemplary aperture **120** including an interior surface **122** of a portable electronic device for receiving a connector including the orientation member **280** of FIG. 4. FIG. 7B shows a sectional view of another exemplary port of a portable electronic device receiving the orientation member **294** of FIG. 6A. As indicated in FIG. 7B, interior surface **122** of aperture **120** includes receiving slots **124** configured to receive and releasably secure attachment ends **296** of attachment arms **294**.

Referring again to FIG. 2D, in one exemplary embodiment, the sealing connector **200** is assembled by placing the orientation member **280** into the receiver **260**. Locking tabs **290** and ridges **270** secure the orientation member in position in the interior **268** of receiver **260**. The gasket **230** is placed in to the interior cavity **218** of plastic sleeve **210** while plastic sleeve **210** is in the open configuration. Gasket **230** may be secured to the plastic sleeve **210** with a suitable adhesive. O-ring **246** of gasket **230** is then positioned in O-ring channel **264** of receiver **260**, and receiver **260** is positioned in the interior cavity **236** of gasket **230** such that the plurality of ridges **244** of gasket **240** are received within channels **262** of receiver **260**. Receiver **260** may be secured to the gasket **230** with a suitable adhesive. The seal **250** is then secured to a front face **266** of receiver **260** with a suitable adhesive.

Referring next to FIG. 2G, the reciprocal connector **142** of reciprocal connector assembly **140** is inserted through the interior of hollow body member **282** of orientation member **280** (or hollow body member **282** of orientation member **292** or orientation member **298**) until the face portion **146** is positioned against depth arms **284**. Reciprocal connector is positioned in the orientation member **280** by aligning tabs **286** and aligning tabs **288**. Depth arms **284** prevent reciprocal connector assembly **140** from pushed too far through sealing connector **200**. The sealing connector **200** is then closed and latch **214** of sleeve **210** is secured. Referring to FIG. 2H, a user then inserts reciprocal connector **142** into aperture **120** and operably connects reciprocal connector **142** into device connector **102** of portable electronic device **100**. Gap **123** is sealed by seal **250** positioned in aperture **120** of case **110**, as illustrated in FIG. 2H.

If an orientation member with attachment tabs **294** (see FIGS. 5A-6B) is used, attachment ends **296** are received within receiving slots **124** of interior surface **122** of aperture **120** to releasably secure the sealing connector **200** to case **110**.

The above figures may depict exemplary configurations for an apparatus of the disclosure, which is done to aid in understanding the features and functionality that can be included in the housings described herein. The apparatus is not restricted to the illustrated architectures or configurations, but can be implemented using a variety of alternative architectures and configurations. Additionally, although the apparatus is described above in terms of various exemplary embodiments and implementations, it should be understood that the various features and functionality described in one or more of the individual embodiments with which they are described, but instead can be applied, alone or in some combination, to one or more of the other embodiments of the disclosure, whether or not such embodiments are described and whether or not such features are presented as being a part of a described embodiment. Thus the breadth and scope of the present disclosure, especially in any following claims, should not be limited by any of the above-described exemplary embodiments.

Terms and phrases used in this document, and variations thereof, unless otherwise expressly stated, should be construed as open ended as opposed to limiting. As examples of the foregoing: the term "including" should be read to mean "including, without limitation" or the like; the term "example" is used to provide exemplary instances of the item in discussion, not an exhaustive or limiting list thereof; and adjectives such as "conventional," "traditional," "standard," "known" and terms of similar meaning should not be construed as limiting the item described to a given time period or to an item available as of a given time, but instead

should be read to encompass conventional, traditional, normal, or standard technologies that may be available or known now or at any time in the future. Likewise, a group of items linked with the conjunction “and” should not be read as requiring that each and every one of those items be present in the grouping, but rather should be read as “and/or” unless expressly stated otherwise. Similarly, a group of items linked with the conjunction “or” should not be read as requiring mutual exclusivity among that group, but rather should also be read as “and/or” unless expressly stated otherwise. Furthermore, although item, elements or components of the disclosure may be described or claimed in the singular, the plural is contemplated to be within the scope thereof unless limitation to the singular is explicitly stated. The presence of broadening words and phrases such as “one or more,” “at least,” “but not limited to” or other like phrases in some instances shall not be read to mean that the narrower case is intended or required in instances where such broadening phrases may be absent. Additionally, where a range is set forth, each of the upper and lower limits of the stated range are inclusive of all of the intermediary units therein.

The foregoing description is intended to illustrate but not to limit the scope of the disclosure, which is defined by the scope of the appended claims. Other embodiments are within the scope of the following claims.

What is claimed:

1. A connector for connecting a reciprocal connector to a device connector of a portable electronic device accessed through an aperture of a protective case, the connector comprising:

- a sleeve for receiving at least a portion of the reciprocal connector;
- an orientation member including a hollow body member configured to receive at least a portion of the reciprocal connector, the orientation member including one or more depth arms configured to contact a face portion of the reciprocal connector and resist movement of the reciprocal connector in a first direction; and
- a seal positioned between the sleeve and the device connector, the seal fluidly sealing the aperture of the protective case.

2. The connector of claim 1, wherein the hollow body member has a substantially rectangular cross-section.

3. The connector of claim 1, wherein the orientation member further comprises one or more attachment tabs extending from the hollow body member, each attachment tab including an attachment end configured to be received within a corresponding receiving slot of the aperture to removably secure the connector to the case.

4. The connector of claim 1, further comprising a receiver surrounding the orientation member, the seal being attached to a front face of the receiver.

5. The connector of claim 1, further comprising a gasket at least partially positioned in an interior of the sleeve, the gasket configured to fluidly seal the interior of the sleeve when the sleeve is in a closed configuration.

6. The connector of claim 5, wherein the gasket comprises a plurality of resilient ridges configured to contact a cord of the reciprocal connector to fluidly seal the interior of the sleeve when the sleeve is in a closed configuration.

7. The connector of claim 5, wherein the gasket comprises an O-ring configured to be positioned around at least a

portion of the reciprocal connector, the O-ring configured to fluidly seal the interior of the sleeve when the sleeve is in a closed configuration.

8. The connector of claim 1, wherein the orientation member further comprises a first pair of aligning tabs configured to contact a portion of the reciprocal connector when the reciprocal connector is received by the orientation member, the first pair of aligning tabs further configured to center and hold the contacted portion of the reciprocal connector along a first axis within the hollow body member of the orientation member.

9. The connector of claim 8, wherein the orientation member further comprises a second pair of aligning tabs configured to contact a second portion of the reciprocal connector when the reciprocal connector is received by the orientation member, the second pair of aligning tabs further configured to center and hold the second contacted portion of the reciprocal connector along a second axis within the hollow body member of the orientation member.

10. The connector of claim 9, wherein the second axis is perpendicular to the first axis.

11. The connector of claim 1, wherein the sleeve includes a living hinge configured to allow the sleeve to move between an open configuration for receiving the portion of the reciprocal connector and a closed configuration for fluidly sealing an interior of the sleeve.

12. The connector of claim 11, further comprising a latch for reversibly securing the sleeve in the closed configuration.

13. A connector for positioning a reciprocal connector in a predetermined position, the connector comprising:

- a hollow body member having an interior configured to receive at least a portion of the reciprocal connector within the interior; and

- one or more depth arms extending from the hollow body member, the depth arms configured to contact a face portion of the reciprocal connector and resist movement of the reciprocal connector in a first direction;

- a first pair of aligning tabs configured to contact a first portion of the reciprocal connector when the reciprocal connector is received in the interior, the first pair of aligning tabs further configured to center and hold the first portion of the reciprocal connector along a first axis within the interior of the hollow body member; and
- a second pair of aligning tabs configured to contact a second portion of the reciprocal connector when the reciprocal connector is received in the interior, the second pair of aligning tabs further configured to center and hold the second portion of the reciprocal connector along a second axis within the interior of the hollow body member.

14. The connector of claim 13, wherein the second axis is perpendicular to the first axis.

15. The connector of claim 13, wherein the hollow body member has a substantially rectangular cross-section.

16. The connector of claim 13 further comprising one or more attachment tabs extending from the hollow body member.

17. The connector of claim 16, wherein each attachment tab terminates in an end having a substantially triangular cross-section.